

SCHEDULE OF MEMBERS		
TOP CHORD	HSS 9 x 9 x 3/8	
BOTTOM CHORD	HSS 9 x 9 x 3/8	
VERTICAL	HSS 7 x 7 x 3/16	
DIAGONAL	HSS 4 x 4 x 1/8	
FLOOR BEAM	W 10 x 30	
FLOOR DIAGONAL	W 6 x 12	



BRIDGE SECTION (Located in Center Panel)

NOTE:

HSS MEMBERS SHALL BE MADE OF A500 GRADE C, WITH YIELD STRESS OF 50 KSI AND TENSILE STRESS OF 62 KSI.

CONCRETE SHALL BE TESTED TO HAVE COMPRESSIVE STRENGTH OF 3000 PSI.

CONNECTIONS SHALL BE DESIGNED IN ACCORDANCE TO AISC STEEL CONSTRUCTION MANUAL, 15TH EDITION - SPECIFICATION CHAPTER K.

Structural Improvement Design for Northern Strand Community Trail Bridge over Saugus River

Team Members: Sean Burke Marlies de Jong Ben Leveillee

Date: March 1, 2019

SHEET 1 OF 3



TOP & BOTTOM CHORDS	
Vertical 1 (V1)	4'
Vertical 2 (V2)	7'
Vertical 3 (V3)	9.5'
V4	11'
V5	12.25'
V6	13'
V7	13'
V8	12.25'
V9	11'
V10	9.5'
V11	7'
V12	4'



NOTE:

HSS MEMBERS SHALL BE MADE OF A500 GRADE C, WITH YIELD STRESS OF 50 KSI AND TENSILE STRESS OF 62 KSI.

CONCRETE SHALL BE TESTED TO HAVE COMPRESSIVE STRENGTH OF 3000 PSI.

CONNECTIONS SHALL BE DESIGNED IN ACCORDANCE TO AISC STEEL CONSTRUCTION MANUAL, 15TH EDITION -SPECIFICATION CHAPTER K.

Structural Improvement Design for Northern Strand Community Trail Bridge over Saugus River

Team Members: Sean Burke Marlies de Jong Ben Leveillee

Date: March 1, 2019

SHEET 2 OF 3



NOTE:

HSS MEMBERS SHALL BE MADE OF A500 GRADE C, WITH YIELD STRESS OF 50 KSI AND TENSILE STRESS OF 62 KSI.

CONCRETE SHALL BE TESTED TO HAVE COMPRESSIVE STRENGTH OF 3000 PSI.

CONNECTIONS SHALL BE DESIGNED IN ACCORDANCE TO AISC STEEL CONSTRUCTION MANUAL, 15TH EDITION -SPECIFICATION CHAPTER K.

Structural Improvement Design for Northern Strand Community Trail Bridge over Saugus River

Team Members: Sean Burke Marlies de Jong Ben Leveillee

Date: March 1, 2019

SHEET 3 OF 3